

Date of Issue: October 2010

Affected Publication: API Specification 11B, *Specification for Sucker Rods, Polished Rods and Liners, Couplings, Sinker Bars, Polished Rod Clamps, Stuffing Boxes, and Pumping Tees*, Twenty-seventh Edition, May 2010

ERRATA

Page 20, **Relationship Column**, Pin pitch diameter tolerance should read:

$$\left(\begin{array}{l} 0.0015\sqrt[3]{D} \\ +0.0015\sqrt[3]{L_e} \\ +0.0015\sqrt[3]{p^2} \end{array} \right) \text{ in.}$$

Page 22, **A.5 Dimensional Inspection** replace the paragraph to read:

Sucker rods shall be inspected according to Table A.6. When a micrometer or caliper is used to measure a circular feature, and a single diameter measurement is out of tolerance then a minimum of two additional measurements, approximately 120 degrees apart, shall be taken. The measurements shall be averaged to determine the nominal dimension. If a gap gauge is used to measure a circular feature and the product is found to be out of tolerance then a micrometer or caliper shall be used as specified above.

Page 30, **Table B.1**, the title should read:

General Dimensions and Tolerances for Polished Rods

Page 39, **Table C.1**, the measurements for $\frac{5}{16}$ in., in the Full Size section of the table, D_2 minimum row to read:

in.	mm
1.250	31.75

Page 39, **Table C.1**, the measurements for $\frac{7}{16}$ in., in the Full Size section of the table, D_2 minimum row to read:

in.	mm
1.625	41.28