

Date of Issue: November 2020

Affected Publication: API Specification 20F, *Corrosion Resistant Bolting for Use in the Petroleum and Natural Gas Industries*, Second Edition, May 2018

Errata 1

Section 1: Section 1.5 (Application of the API Monogram) shall be deleted.

Table 3: The table shall be changed as indicated in the red boxes:

Table 3—API 6ACRA and UNS R30035 Grade Identification Markings

API 6ACRA or UNS and Material Designation	Marking
N07716 120K	N1A
N07716 140K	N1B
N07718 120K	N2A
N07718 140K	N2B
N07725 120K	N3A
N09925 110K	N4A
N09935 110K	N5A
N09945 125K	N6A
N09946 140K	N7A
N09946 150K	N7B
N09946 160K	N7C
R30035 work strengthen only	R3A
R30035 work strengthen and aged 1300 °F	R3B
R30035 work strengthen and aged 1350 °F	R3C
R30035 work strengthen and aged 1425 °F	R3D
R30035 work strengthen and aged 1450 °F	R3E
R30035 work strengthen and aged 1475 °F	R3F
R30035 work strengthen and aged 1500 °F	R3G

Section 8: The clause number associated with the section titled “Additional Marking Required by this Standard” shall be updated to 8.2, as follows:

8.2 Additional Marking Required by this Standard

Annex A: The text of this annex shall be deleted, and a placeholder shall be added, as follows:

Annex A
(informative)

API Monogram Program
Use of the API Monogram by Licensees

The information in this annex has been intentionally removed.

See API Specification Q1 (Annex A) or the API website for information pertaining to the API Monogram Program and use of the API Monogram on applicable products.