

If you have any questions or comments regarding API standards, please visit https://www.api.org/products-and-services/standards

UPSTREAM SAFETY STANDARDS

RP 54

Occupational Safety and Health for Oil and Gas Well Drilling and Servicing Operations

(includes Addendum 1 dated June 2021)

Recommends practices and procedures for promoting and maintaining safe and healthy working conditions for personnel in drilling and well servicing operations. These recommendations apply to rotary drilling rigs, well servicing rigs, and special services as they relate to operations on location. It is intended that the applicable requirements and recommendations of some sections of the standard be applied, as appropriate, to other sections. The recommendations are not intended to cover seismic drilling or water well drilling operations. These recommendations do not apply to site preparation and site remediation operations. Pages: 62

4th Edition | February 2019 | Product Number: G54004 | Price: \$140.00

Std 65-2 ◆

Isolating Potential Flow Zones During Well Construction

Contains best practices for zone isolation in wells to prevent annular pressure and/or flow through or past pressure-containment barriers that are installed and verified during well construction. Well construction practices that may affect barrier sealing performance are mentioned along with methods to help ensure positive effects or to minimize any negative ones. The objectives of this guideline are two-fold. The first is to help prevent and/or control flows just prior to, during, and after primary cementing operations to install or "set" casing and liner pipe strings in wells. The second objective is to help prevent sustained casing pressure (SCP). The guidance from this document covers recommendations for pressure-containment barrier design and installation and well construction practices that affect the zone isolation process to prevent or mitigate annular fluid flow or pressure. Pages: 83

2nd Edition | December 2010 | Reaffirmed: November 2016 Product Number: G65202 | Price: \$141.00

You may download a PDF of this document from https://www.api.org/oil-andnatural-gas/wells-to-consumer/exploration-and-production/hydraulicfracturing/65-2-isolating-potential-flow-zones

RP 65-3

Wellbore Plugging and Abandonment

Provides guidance for the design, placement, and verification of cement plugs in wells to be temporarily or permanently abandoned, as well as remediation and verification of annular barriers. Wells temporarily abandoned (suspended) are intended to be re-entered in the future. The placement of barriers may depend on whether the well is to be temporarily or permanently abandoned. Cement plug lengths are not considered in this document. Pages: 52

1st Edition | June 2021 | Product Number: G65301 | Price: \$112.00

RP 67

Recommended Practice for Oilfield Explosives Safety

Applicable to chemical explosives used as an energy source to do work in oil- and gas-producing operations, and more specifically to explosives intended for use inside a wellbore. The purpose of this recommended practice (RP) is primarily to prevent the inadvertent initiation of these explosives at the wellsite but also includes some recommendations for safe and secure storage and transportation and handling, as well as requirements for design and manufacture of selected equipment.

While some chemicals intended for various nonexplosive applications can prove explosive when misused (such as lithium batteries), it is not the intent of this RP to address these materials. Pages: 85

3rd Edition | October 2019 | Product Number: G06703 | Price: \$121.00

RP 74

RP 75

Recommended Practice for Occupational Safety for Onshore Oil and Gas Production Operation

Recommends practices and procedures for promoting and maintaining safe working conditions for personnel engaged in onshore oil and gas production operations, including special services. Pages: 23

1st Edition | October 2001 | Reaffirmed: January 2013 Product Number: G74001 | Price: \$67.00

Safety and Environmental Management System for Offshore Operations and Assets

Provides companies engaged in offshore operations with a framework for the establishment, implementation, and maintenance of a Safety and Environmental Management System (SEMS) to manage and reduce risks associated with safety and the environment to prevent incidents and events.

This recommended practice applies, in part or whole, to companies engaged in offshore operations, from lease evaluation through decommissioning.

This document is not intended to be prescriptive or limiting on the expectations of each SEMS element; rather, it allows flexibility appropriate to the size, scope, and risk of a Company's assets and operations. It is advised that users of this document review and comply with applicable legal and regulatory requirements, and conform with applicable industry codes and standards.

Consideration may be given to using this document to help systematically manage other aspects of operations, such as security and health. Pages: 34

4th Edition | December 2019 | Product Number: G07504 | Price: \$110.00

Bull 75L

Guidance Document for the Development of a Safety and Environmental Management System for Onshore Oil and Natural Gas Production Operations and Associated Activities

Provides general information and guidance for the development of a safety and environmental management system (SEMS) for onshore oil and natural gas operations, including drilling, production, and well servicing activities. Although there is an extensive amount of information that has been developed on the topic of safety and environmental management systems, this document focuses on this industry sector to help foster continuous improvement in our industry's safety and environmental performance. It is recognized that many onshore oil and natural gas companies have effective SEMS in place; however, the intent of this document is to provide an additional tool that can assist these and especially other operators in taking the next step toward implementing a complete system at a pace that complements their business plan. For those who already have a mature SEMS in place, this document can be used for continuous improvement of the system. Pages: 12

1st Edition | November 2007 | Product Number: G75L01 | Price: \$37.00

To purchase individual API standards, visit apiwebstore.org

RP 76

Contractor Safety Management for Oil and Gas Drilling and Production Operations

Intended to assist operators, contractors, and subcontractors (third parties) in the implementation of a contractor safety program and improve the overall safety performance while preserving the independent contractor relationship. It is intended for the Upstream Segment of the petroleum industry; however, since the operator requirements and the contracted work are diverse, this publication may not be applicable to all operations at each company or to all contract work performed in those operations. Many oil and gas exploration and production companies contract for equipment and personnel services for a wide range of activities, including drilling production, well servicing, equipment repair, maintenance, and construction. Certain activities of contractors have the potential to take place either contractor and/or operator personnel and/or equipment at risk. It is important that operations are carried out in a safe manner. Operators and contractors need to provide safe work places and to protect the safety of their work places and to protect the safety of their workforces and the general public. When they work together to improve safety, both benefit. Pages: 60

2nd Edition | November 2007 | Reaffirmed: January 2013 Product Number: G07602 | Price: \$62.00

MULTI-SEGMENT PUBLICATIONS

Firefighting Foam Transition Guidance

Provides the industry with suggestions and considerations for the transition from C8 legacy fluorinated foams concentrates to another type of foam concentrate [such as C6 or synthetic fluorine-free foam (SFFF)]. For each step of the MOC, a separate document is available that provides considerations and examples on how an entity may choose to execute the transition. While it is ideal to have a drop-in foam concentrate replacement with minimum changes in processes or practices to use during this transition, the MOC process plans for any changes that must be accounted for Pages: 32

October 2020 | To obtain a copy of this report, please visit https://www.api.org/-/media/Files/Oil-and-Natural-Gas/Refining/Fire-fighting-Foam-Transition-Guidance-October-2020.pdf

RP 752

Management of Hazards Associated with Location of Process Plant Permanent Buildings

Provides guidance for managing the risk from explosions, fires and toxic material releases to on-site personnel located in new and existing buildings intended for occupancy. This RP was developed for use at refineries, petrochemical and chemical operations, natural gas liquids extraction plants, natural gas liquefaction plants, and other onshore facilities covered by the OSHA Process Safety Management of Highly Hazardous Chemicals, 29 *CFR* 1910.119.

Buildings covered by this RP are rigid structures intended for permanent use in fixed locations. Tents, fabric enclosures and other soft-sided structures are outside the scope of this document. This 3rd Edition of RP 752:2009 supersedes all previous editions, including the technical data provided in those documents.

Significant research and development of technology pertinent to building siting evaluations has been performed since the publication of the previous editions of RP 752. Examples of updated technology include prediction of blast damage to buildings, determination of occupant vulnerabilities, and estimates of event frequencies. Prior versions of RP 752 and the technical data included in them should not be used for building siting evaluations. The 2nd Edition of RP 752 covered all building types both permanent and portable. This 3rd Edition of RP 752 does not cover portable buildings. Portable buildings are now covered by RP 753. It is recognized, however, that

portable buildings specifically designed for significant blast load represent a potential area of overlap between RP 753 and RP 752. In accordance with 1.3 of this document:

"Buildings described in API RP 753, Management of Hazards Associated with Location of Process Plant Portable Buildings, First Edition, June 2007, as 'portable buildings specifically designed to resist significant blast loads' and intended for permanent use in a fixed location are covered in this document (API RP 752). All other portable buildings are covered by API RP 753." Pages: 27

3rd Edition | December 2009 | Reaffirmed: August 2020 Product Number: K75203 | Price: \$153.00

RP 753

Management of Hazards Associated with Location of Process Plant Portable Buildings

Provides guidance for reducing the risk to personnel located in portable buildings from potential explosion, fire and toxic release hazards. While occupied permanent buildings (e.g. control rooms, operator shelters) located near covered process area are typically constructed to be blast and fire resistant, conventional portable buildings (i.e. light wood trailers) are typically not constructed to be blast and fire resistant. Past explosion accidents have demonstrated that occupants of conventional portable buildings are susceptible to injuries from structural failures, building collapse, and building debris and projectiles.

Guidance is provided based on the following principles.

- Locate personnel away from covered process areas consistent with safe and effective operations.
- Minimize the use of occupied portable buildings in close proximity to covered process areas.
- Manage the occupancy of portable building especially during periods of increased risk including unit start up or planned shut-down operations.
- Design, construct, install, and maintain occupied portable buildings to protect occupants against potential hazards.
- Manage the use of portable buildings as an integral part of the design, construction, and maintenance operation of a facility. Pages: 22

1st Edition | June 2007 | Reaffirmed: August 2020 Product Number: K75301 | Price: \$153.00

RP 754

Process Safety Performance Indicators for the Refining and Petrochemical Industries (ANSI/API RP 754)

Identifies leading and lagging process safety indicators useful for driving performance improvement. As a framework for measuring activity, status, or performance, this document classifies process safety indicators into four tiers of leading and lagging indicators. Tiers 1 and 2 are suitable for nationwide public reporting and Tiers 3 and 4 are intended for internal use at individual facilities. Guidance on methods for development and use of performance indicators is also provided. This RP was developed for the refining and petrochemical industries, but may also be applicable to other industries with operating systems and processes where loss of containment has the potential to cause harm. Applicability is not limited to those facilities covered by the OSHA Process Safety Management Standard, 29 *CFR* 1910.119, or similar national and international regulations. Pages: 134

3rd Edition | August 2021 | Product Number: K75403 | Price: \$182.00

To purchase individual API standards, visit apiwebstore.org

RP 755

Fatigue Risk Management Systems for Personnel in the Refining and Petrochemical Industries

(ANSI/API RP 755)

Provides guidance to all stakeholders (e.g. employees, managers, supervisors) on understanding, recognizing, and managing employee fatigue in the workplace. Should sites decide to use this document, the owners/operators shall establish policies and procedures to meet the purpose of this recommended practice.

This document was developed for refineries, petrochemical and chemical operations, natural gas liquefaction plants, and other facilities such as those covered by the OSHA Process Safety Management Standard, 29 *CFR* 1910.119. This document is intended to apply to a workforce that is commuting daily to a job location.

ANSI/API RP 755 applies to all employees working night shifts, rotating shifts, extended hours/days, or call outs who are involved in process safety-sensitive actions. It should also be considered for others making process safety-sensitive decisions. On-site contractors involved in process safety-sensitive actions shall have fatigue risk management systems equivalent to the criteria outlined in this document. Pages: 17

2nd Edition | May 2019 | Product Number: K75502 | Price: \$145.00

TR 755-1

Technical Support Document for ANSI/API RP 755, Fatigue Risk Management Systems for Personnel in the Refining and Petrochemical Industries

Identifies and explains the scientific and operational issues considered during the preparation of RP 755. By providing the reasoning behind the specific wording in the RP 755 document, this document supports each key statement in RP 755 in sequence so that it can be used in parallel with the RP 755 text. To make this document accessible and manageable, key scientific sources and references are provided to help readers gain access to the scientific literature.

Fatigue Risk Management Systems (FRMS) have emerged and been widely recognized as a more effective approach to managing and mitigating employee fatigue risk in the 24/7 workplace. The core feature of the FRMS is that it is a data-driven, risk-informed, safety performance-based system. The FRMS implementation process first identifies all sources of fatigue risk in the business operation, then introduces mitigating policies, technologies, and procedures to reduce the risk, and most importantly then maintains them in a proactively managed continuous improvement system. The history of FRMS was recently summarized.

This method represents a significant step change from the traditional approaches of either relying on maximum limits to hours of work or minimum limits to hours of rest (variously called Hours of Service, Work-Rest Rules, Working Time Directives), or adopting intermittent or piece-meal solutions (e.g. a fatigue training program or a shift schedule redesign), depending on the interests and initiative of local site managers.

One essential feature of FRMS is that it is a system meant to be improved upon on a regular and continuous basis. It is not a set of guidelines designed for one-time compliance but instead provides a framework that will evolve over time, driven by the collection of data on fatigue risk and fatigue outcomes (e.g. fatigue-related incidents). Pages: 49

1st Edition | April 2010 | Product Number: K755101 | Price: \$112.00

RP 756

Management of Hazards Associated with Location of Process Plant Tents

Provides guidance for managing the risk from explosions, fires and toxic material releases to on-site personnel located in tents. The term "tent" is used to describe a wide range of structures and is defined in §3.15. This RP was developed for use at refineries, petrochemical and chemical operations, natural gas liquids extraction plants, natural gas liquefaction plants, and other onshore facilities covered by OSHA 29 *CFR* 1910.119. The focus of this RP is primarily on process related hazards. However, non-process related hazards may exist that could present risks to tent occupants. Previous accidents have demonstrated that tent occupants are susceptible to injuries from fires originating inside the tent, from tent collapse due to extreme weather, and from falling objects. Some of these hazards are addressed by tent design standards, manufacturer's recommendations, and local regulations. Pages: 25

1st Edition | September 2014 | Reaffirmed: August 2020 Product Number: C75601 | Price: \$136.00

TR 756-1

Process Plant Tent Responses to Vapor Cloud Explosions—Results of the American Petroleum Institute Tent Testing Program

Beginning in 2011, the American Petroleum Institute (API) to performed vapor cloud explosion (VCE) tests to determine the response of tents to the potential explosion hazards that may be present at refineries, petrochemical and chemical operations, natural gas and other onshore process facilities covered by OSHA 29 CFR 1910.119. The testing was conducted to provide data for use by the API committee developing RP 756. This publication, TR 756-1, contains information on the results of the API tent testing program. Pages: 597

1st Edition | September 2014 | Product Number: C756101 | Price: \$206.00

Publ 770

A Manager's Guide to Reducing Human Errors—Improving Human Performance in the Process Industries

Intended for an audience of middle managers to senior executives who have different levels of knowledge about human factors engineering. It is designed to equip them with a basic understanding of the causes of human errors and to suggest ways for reducing human errors at individual facilities. It also describes how to incorporate human reliability analysis (HRA) into process safety management activities. Pages: 85

1st Edition | March 2001 | Product Number: K77001 | Price: \$82.00

To purchase individual API standards, visit apiwebstore.org

Std 780

Security Risk Assessment Methodology for the Petroleum and Petrochemical Industries

Prepared by a Security Risk Assessment (SRA) Committee of the American Petroleum Institute (API) to assist the petroleum and petrochemical industries in understanding security risk assessment and in conducting SRAs. The standard describes the recommended approach for assessing security risk widely applicable to the types of facilities operated by the industry and the security issues the industry faces. The standard is intended for those responsible for conducting security risk assessments and managing security at these facilities. The method described in this standard is widely applicable to a full spectrum of security issues from theft to insider sabotage to terrorism. The API SRA Methodology was developed for the petroleum and petrochemical industry, for a broad variety of both fixed and mobile applications. This recommended practice describes a single methodology, rather than a general framework for SRAs, but the methodology is flexible and adaptable to the needs of the user. This methodology constitutes one approach for assessing security vulnerabilities at petroleum and petrochemical industry facilities. However, there are other risk assessment techniques and methods available to industry, all of which share common risk assessment elements. Pages: 113

1st Edition | May 2013 | Reaffirmed: February 2022 Product Number: K78001 | Price: \$206.00

RP 2001

Fire Protection in Refineries

Provides a better understanding of refinery fire protection and the steps needed to promote the safe storage, handling, and processing of petroleum and petroleum products in refineries. A basic premise of this standard is that fire prevention provides the fundamental foundation for fire protection.

This publication covers basic concepts of refinery fire protection. It reviews the chemistry and physics of refinery fires; discusses how the design of refinery systems and infrastructure impact the probability and consequences of potential fires; describes fire control and extinguishing systems typically used in refineries; examines fire protection concepts that should be covered in operating and maintenance practices and procedures; and provides information on organization and training for refinery emergency responders.

Many of the concepts, systems, and equipment discussed in this document are covered in detail in referenced publications, standards, or governmental requirements. Pages: 90

10th Edition | July 2019 | Product Number: C200110 | Price: \$180.00

RP 2003

Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents

Presents the current state of knowledge and technology in the fields of static electricity, and stray currents applicable to the prevention of hydrocarbon ignition in the petroleum industry and is based on both scientific research and practical experience. The principles discussed in this recommended practice are applicable to other operations where ignitable liquids and gases are handled. Their use should lead to improved safety practices and evaluations of existing installations and procedures. Pages: 76

8th Edition | September 2015 | Reaffirmed: March 2020 Product Number: K20038 | Price: \$206.00

RP 2009

Safe Welding, Cutting, and Hot Work Practices in the Petroleum and Petrochemical Industries

Provides information to assist in the safe performance of welding, cutting, and other hot work activities to be done safely in petroleum and petrochemical operations. The understanding of potential hazards, and application of this knowledge, can help reduce the probability and severity of incidents and the risk of harmful health effects from those activities. Personnel engaged in hot work should have a comprehensive understanding of the potential hazards associated with the activity and materials involved. RP 2009 was updated to include added precautions to prevent fires and incidents during welding operations, as well as an awareness of the hazards of inhalation of welding fumes. Additionally, it includes specific guidance to evaluate procedures for certain types of work equipment in service, supports UN Sustainable Development Goal #9 for Resilient Infrastructure, and is included in the U.S. Department of Labor OSHA's resources materials for Process Safety Management. Pages: 43

8th Edition | March 2022 | Product Number: K20098 | Price: \$105.00

RP 2027

Ignition Hazards and Safe Work Practices for Abrasive Blasting of Atmospheric Storage Tanks in Hydrocarbon Service

Provides safe work practices for the prevention and control of vapor, ignition, and other potential hazards during abrasive blasting of aboveground storage tanks in liquid hydrocarbon service at atmospheric pressure. It also provides assistance to employers in developing operating procedures that provide for hazard recognition to significantly reduce ignition risks during abrasive blasting of hydrocarbon storage tanks in service that may contain or have the potential to develop a flammable atmosphere in the vapor space. This RP applies to safe work practices required for abrasive blasting of exterior shells and exterior roofs of all aboveground atmospheric storage tanks in liquid hydrocarbon service. It also applies to safe work practices for abrasive blasting conducted on the roofs and inner portions of the exposed surfaces of shells (that portion of the shell above the roof level) on open-top (external) floating roof tanks. This RP also covers recognition and control of ignition hazards that are specific to and may be present during abrasive blasting of aboveground storage tanks in liquid hydrocarbon service at atmospheric pressure. The ignition sources covered in this RP include static electricity, internal combustion engines, electric motors, friction sparks, hot metal surfaces, and external-to-the-work ignition sources. Pages: 27

4th Edition | November 2018 | Product Number: C20274 | Price: \$132.00

RP 2028

Flame Arresters in Piping Systems

Covers the use and limitations of flame arresters installed in piping systems in the petroleum and petrochemical industries. It provides a general overview of flame arresters currently in use and some potential concerns or limitations. Applicable combustion and flame propogation parameters are discussed including the distinction between arresting flames versus arresting detonations. Pages: 12

3rd Edition | February 2002 | Reaffirmed: December 2010 2-Year Extension: February 2015 | Product Number: K20283 | Price: \$65.00

RP 2030

Application of Fixed Water Spray Systems for Fire Protection in the Petroleum and Petrochemical Industries

Provides guidance for the petroleum industry and some petrochemical industry applications (for non-water-reactive petrochemicals with physical and combustion characteristics comparable to hydrocarbons) in determining where water spray systems might be used to provide protection from fire damage for equipment and structures. Pages: 21

4th Edition | September 2014 | Product Number: K20304 | Price: \$114.00

To purchase individual API standards, visit apiwebstore.org

RP 2201

Safe Hot Tapping Practices in the Petroleum and Petrochemical Industries

Provides information to assist in safely conducting hot tapping operations on equipment in service in the petroleum and petrochemical industries. No document can address all situations nor answer all potential questions; however, the understanding of potential hazards, and application of this knowledge, can help reduce the probability and severity of incidents. Pages: 27

5th Edition | June 2003 | Reaffirmed: March 2020

2-Year Extension: February 2015 | Product Number: K22015 | Price: \$94.00

RP 2210

Flame Arresters for Vents of Tanks Storing Petroleum Products

Discusses the benefits and detriments associated with the use of flame arresters on vents utilized on atmospheric fixed-roof tanks. Pages: 4

3rd Edition | June 2000 | Reaffirmed: March 2020 Product Number: K22103 | Price: \$71.00

RP 2217A

Safe Work in Inert Confined Spaces in the Petroleum and Petrochemical Industries

Covers design, materials, face-to-face dimensions, pressure-temperature ratings, and examination, inspection, and test requirements for two types of check valves:

- Type 'A' check valves are short face-to-face and can be: wafer, lug, or double flanged; single plate or dual plate; gray iron, ductile iron, steel, nickel alloy, or other alloy designed for installation between Classes 125 and 250 cast iron flanges as specified in ASME B16.1, between Classes 150 and 300 ductile iron flanges as specified in ASME B16.42, between Classes 150 and 2500 steel flanges as specified in ASME B16.5, and between Classes 150 and 600 steel pipeline flanges as specified in MSS SP-44 or steel flanges as specified in ASME B16.47.
- Type 'B' bolted cover swing check valves are long face-to-face as defined in 5.1.2 and can be: flanged or buttwelding ends of steel, nickel alloy, or other alloy material. End flanges shall be as specified in ASME B16.5 or ends shall be butt-welding as specified in ASME B16.25. Pages: 34

5th Edition | July 2017 | Product Number: K2217A5 | Price: \$157.00

RP 2218

Fireproofing Practices in Petroleum and Petrochemical Processing Plants

Intended to provide guidance for selecting, applying, and maintaining fireproofing systems designed to limit the extent of fire-related property loss from pool fires in the petroleum and petrochemical industries. Where comparable hazards exist, and to the extent appropriate, it may be applied to other facilities that could experience similar severe fire exposure and potential losses.

This RP identifies fireproofing needs for petroleum and petrochemical plants specifically focusing on property loss protection for pool fires scenarios in on-shore processing plants. Pages: 60

3rd Edition | July 2013 | Reaffirmed: March 2020 Product Number: K22183 | Price: \$174.00

RP 2219

Safe Operation of Vacuum Trucks Handling Flammable and Combustible Liquids in Petroleum Service

Provides information concerning the safe operation of vacuum trucks engaged in all aspects of handling flammable and combustible liquids, associated waste water, produced water, sour water, basic sediment and water (BS&W), caustics, spent acids, or other fluids stemming from petroleum operations, products, powders, and the hazard of dust explosions. This publication discusses the types of vacuum pumps and cargo tanks associated with vacuum truck operations, the common hazards associated with those vacuum truck operations, and representative safe work practices and precautions to help prevent accidents and injuries. Appendix G provides

brief descriptions of a variety of incidents involving vacuum trucks, including offloading into open areas. These may be useful in reviewing specific operating procedures or developing materials for safety meetings or pre-job briefings. Pages: 60

4th Edition | June 2016 | Product Number: K22194 | Price: \$179.00

Publ 2375

1996 Summary of U.S. Occupational Injuries, Illnesses, and Fatalities in the Petroleum Industry

This annual summary reports on cases recordable in 1996 under the U.S. Bureau of Labor Statistics' recordkeeping guidelines. The survey is based on data submitted to the American Petroleum Institute by 176 oil and gas companies, employing 285,885 persons. The report includes information regarding injuries, illnesses, fatalities, lost workday cases, and incidence rates by function.

June 1997 | Product Number: K23751 | Price: \$104.00

Publ 2376

1997 Summary of U.S. Occupational Injuries, Illness, and Fatalities in the Petroleum Industry

June 1998 | Product Number: K23761 | Price: \$104.00

Publ 2377

1998 Summary of U.S. Occupational Injuries, Illness, and Fatalities in the Petroleum Industry

March 1999 | Product Number: K23771 | Price: \$112.00

Publ 2378

1999 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

June 2000 | Product Number: K23781 | Price: \$112.00

Publ 2379

2000 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

March 2001 | Product Number: K23790 | Price: \$112.00

Publ 2380

2001 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

March 2002 | Product Number: K23801 | Price: \$112.00

Publ 2381

2002 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

June 2003 | Product Number: K23811 | Price: \$112.00

Publ 2382

2003 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

May 2004 | Product Number: K23821 | Price: \$112.00

Publ 2383

2004 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

March 2005 | Product Number: K23831 | Price: \$112.00

To purchase individual API standards, visit apiwebstore.org

Publ 2384

2005 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

This annual summary reports on cases recordable in 2005 under the US Bureau of Labor Statistics' record keeping guidelines. The survey is based on data submitted to the American Petroleum Institute by oil and gas companies. The report includes information regarding injuries, illness, and fatalities, lost workday cases, and incidence rates by function.

May 2006 | Product Number: K23841 | Price: \$112.00

Publ 2385

2006 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

June 2007 | Product Number: K23851 | Price: \$112.00

Publ 2386

2007 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

May 2008 | Product Number: K23861 | Price: \$112.00

Publ 2387

2008 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

March 2009 | Product Number: K23871 | Price: \$112.00

Publ 2388

2009 Survey on Petroleum Industry Occupational Injuries, Illness, and Fatalities Summary Report: Aggregate Data Only

Reports on cases recordable in 2009 under the U.S. Bureau of Labor Statistics' recordkeeping guidelines. The survey is based on data submitted to API by oil and gas companies. The report includes information regarding injuries, illness, and fatalities, lost workday cases, and incidence rates by function.

April 2010 | Product Number: K23881 | Price: \$112.00

1989 Summary of Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

January 1989 | Product Number: K19996 | Price: \$64.00

1990 Summary of Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

July 1991 | Product Number: K19988 | Price: \$89.00

1991 Summary of Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

September 1992 | Product Number: K19987 | Price: \$89.00

1992 Summary of Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

August 1993 | Product Number: K19986 | Price: \$89.00

1993 Summary of Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

June 1994 | Product Number: K19985 | Price: \$104.00

1994 Summary of U.S. Occupational Injuries, Illnesses and Fatalities in the Petroleum Industry

June 1995 | Product Number: K19984 | Price: \$104.00

1995 Summary of U.S. Occupational Injuries, Illnesses, and Fatalities in the Petroleum Industry

May 1996 | Product Number: K19983 | Price: \$104.00

Publ 2510A

Fire Protection Considerations for the Design and Operation of Liquefied Petroleum Gas (LPG) Storage Facilities

Supplements Std 2510 and addresses the design, operation, and maintenance of liquefied petroleum gas (LPG) storage facilities from the standpoint of prevention and control of releases, fire protection design, and fire control measures. The history of LPG storage facility safety experience, facility design philosophy, operating and maintenance procedures, and various fire protection and fire-fighting approaches are presented. The storage facilities covered are LPG installations (storage vessels and associated loading/unloading/transfer systems) at marine and pipeline terminals, natural gas processing plants, refineries, petrochemical plants, and tank farms. Pages: 45

2nd Edition | December 1996 | Reaffirmed: December 2015

Product Number: K2510A | Price: \$110.00

STORAGE TANK SAFETY STANDARDS

Std 2015 ◆

Requirements for Safe Entry and Cleaning of Petroleum Storage Tanks

Applicable to stationary atmospheric and low-pressure (up to and including 15 psig) aboveground petroleum storage tanks used in all sectors of the petroleum and petrochemical industry, including crude oil and gas production; refining; petrochemicals; pipelines and terminals; bulk storage; and ethanol facilities. This standard provides requirements for safely planning, coordinating, and conducting tank entry and cleaning operations, from removal from service through return to service. Pages: 146

8th Edition | January 2018 | Product Number: K20158 | Price: \$215.00

RP 2021

Management of Atmospheric Storage Tank Fires

Provides experience-based information to enhance the understanding of fires in atmospheric storage tanks containing flammable and combustible materials. It presents a systematic management approach that can assist tank fire prevention. If fires do occur, this information can help responders optimize fire suppression techniques to reduce the severity of an incident and reduce the potential for escalation. Pages: 83

4th Edition | May 2001 | Reaffirmed: March 2020 Product Number: K20214 | Price: \$145.00

RP 2026 ◆

Safe Access/Egress Involving Floating Roofs of Storage Tanks in Petroleum Service

Addresses the hazards associated with access/egress onto external and internal floating roofs of in-service petroleum storage tanks and identifies some of the most common practices and procedures for safely accomplishing this activity. This RP is intended primarily for those persons who are required to perform inspection, service, maintenance, or repair activities that involve descent onto floating roofs of in-service petroleum tanks. Pages: 28

4th Edition | July 2022 | Product Number: K202604 | Price: \$110.00

RP 2207 ◆

Preparing Tank Bottoms for Hot Work

Addresses only the safety aspects of hot work performed on petroleum storage tank bottoms. It discusses safety precautions for preventing fires, explosions, and associated injuries. The term "hot work," as used in this publication, is defined as an operation that can produce a spark or flame hot enough to ignite flammable vapors. RP 2009 provides more in-depth information on safe hot work practices, and its requirements are not duplicated here. Pages: 28

8th Edition | April 2022 | Product Number: K22078 | Price: \$121.00

To purchase individual API standards, visit apiwebstore.org

Std 2350

Overfill Protection for Storage Tanks in Petroleum Facilities (includes Errata 1 dated April 2021) (ANSI/API Std 2350)

Applies to storage tanks associated with marketing, refining, pipeline, and terminals operations and with tanks containing Class I or Class II petroleum liquids and use is recommended for Class III petroleum liquids. This standard addresses overfill protection for petroleum storage tanks. It recognizes that prevention provides the most basic level of protection, thus while using both terms "protection" and "prevention," the document emphasizes prevention. The standard's scope covers overfill (and damage) prevention practices for aboveground storage tanks in petroleum facilities, including refineries, marketing terminals, bulk plants, and pipeline terminals that receive flammable and combustible liquids. The fourth edition continues to build on experience and new technology through the use of management systems. Since operations are the primary overfill prevention safeguard, new definitions and requirements are established for alarms. Risk reduction is also addressed by current and generally accepted industry practices.

The essential elements of this document are based on current industry safe operating practices and existing consensus standards. Federal, state, and local regulations or laws may contain additional requirements for tank overfill protection programs. For existing facilities, the results of a risk-based analysis of aboveground atmospheric petroleum storage tanks may indicate the need for more protection against overfilling. In such cases, some provisions from this standard may be suitable.

The purpose of this standard is to assist owner/operators and operating personnel in the prevention of tank overfills by implementation of a comprehensive overfill prevention process (OPP). The goal is to receive product into the intended storage tank without overfill or loss of containment.

This standard does not apply to: underground storage tanks; aboveground tanks of 1320 U.S. gallons (5000 liters) or less; aboveground tanks which comply with PEI 600; pressure vessels; tanks containing non-petroleum liquids; tanks storing LPG and LNG; tanks at service stations; tanks filled exclusively from wheeled vehicles (i.e. tank trucks or railroad tank cars); and tanks covered by OSHA 29 CFR 1910.119 and EPA 40 CFR 68, or similar regulations. Pages: 75

5th Edition | September 2020

Product Number: K235005 | Price: \$135.00