



General Information

1-Testing Company	2-Perforating System Description (Include gun and charge name)	3-Test Location (City, State, Country)
-------------------	--	--

1. CHARGE SELECTION – Mandatory activity to witness, API RP 19B, Section 1.4

1-Date	2-Location (If different from test location)	3-Charge Description	4-Charge Part #	5-Date Shift Code
6-Quantity of Charges Available for Selection Process (# boxes, charges/box, etc.) (Minimum required is 300)				
7-Quantity of Charges Selected (Describe how selected, ex. 4 from box 001, 4 from box 006, etc. Also indicate how many selected for gun, and how many for QC shots)				
8-Sealing of Selected Charges (Describe how sealed and marked, for reference by witness of gun loading & QC shot; ex. all selected charges placed inside new charge box, QC charges labeled w/ blue "QC" written on case, box taped shut with witnesses' signature and date on tape)				
9-Miscellaneous comments on Charge Selection				

Witness Information

10-Name	11-Company	12-Signature
13-Name	14-Company	15-Signature

2. GUN LOADING – Mandatory activity to witness, API RP 19B, Section 1.3

1-Date	2-Gun Description	3-Gun OD	4-Phasing	5-Shot Density (spf)	6-# of Charges Loaded
7-Hardware Verified as Standard Field Equipment? (Y / N) How Verified? (Describe reference material for verification; ex. Field Catalog, Engineering File, etc. List which components were verified. At minimum, include carrier, adapters, and detonating cord. If gun to be positioned for test, standoff adapters should be verified)					
8-Scallop Depth Verified? (Y / N)	9-Scallop Diameter Verified? (Y / N)	10-Gun ID Verified? (Y / N)	11-OD of Standoff Hardware (measured over fins):		
12-Detonating Cord Description:					
13-Describe how charges verified to be same as those selected by witness? (Either charge selection done at same time as gun loading and in sight all time since selected, or seal / marking must match description in Charge Selection Section.)					
14-Loaded interval marked on outside of gun? (Y / N) How marked? (At minimum, top shot should be marked for verification of gun orientation at time of test)					
15-If gun loaded before test date, gun must be sealed to prevent tampering. Describe how sealed for reference by test witness. (Ex. Clear packing tape over top and bottom adapter-carrier connection with all witnesses signatures on tape)					
16-Miscellaneous comments on Gun Loading					

Witness Information

17-Name	18-Company	19-Signature
20-Name	21-Company	22-Signature

Witness's Initials:

Client's Initials:

GENERAL INFORMATION

1-Testing Company	2-Perforating System Description (Include gun and charge name)	3-Test Location (City, State, Country)
-------------------	--	--

3. GUN FIRING / DATA COLLECTION – Mandatory activity to witness, API RP 19B, Sections 1.8, 1.9 and 1.10

1-Date	2-Target Diameter	3-Casing Diameter	4-Casing Wall
5-Casing (verify that the casing used in the construction of the target meets the reported grade and weight)			
6-Steel form or culvert Witness must verify and record that steel form or culvert remains intact during test (Y / N)			
7-Describe how gun verified to be same as one witnessed loaded? (Either gun in sight all time since loading, or seal / marking must match description in Gun Loading Section.)			
8-Minimum gun-casing standoff	9-Top-shot oriented with minimum standoff? (Y / N)	10-Casing full of water? (Y / N)	11-Distance – Top of target to top shot (must be greater than 12 in.)
12-Penetration Measurements (Witness all measurements recorded)			
13-EH Measurements (Witness all measurements recorded)			
14-Completed datasheet provided? (Y / N)			
15-Miscellaneous comments on Gun Firing / Data Collection			

Concrete Slurry Information

15-Date poured	16-Amount of cement (include unit of measure)	17-Amount of sand (include unit of measure)	18-Amount of water (include unit of measure)
19-Sand / Cement Ratio (Divide amount of sand by amount of cement. Specification is between 2.02 and 1.98)			
20-Water / Cement Ratio (Divide amount of water by amount of cement. If water amount given in gallons, multiply by 8.34 (lb/gal) to get amount water in lbs. Specification is between 0.5252 and 0.5148). Must be documented as 4 decimal points, ex: 0.xxxx			
21-Cement Type (Verify cement conforms to API Class A or Type 1)		22-Frac Sand (Verify that the 16-30 Frac Sand conforms to specification API RP56 Second Edition 1995)	

Witness Information

23-Name	24-Company	25-Signature
26-Name	27-Company	28-Signature

4. QC SHOTS – Mandatory activity to witness, API RP 19B, Section 1.9d

1-Date	2-Location (If different from test location)	3-Charge Description	4-Charge Part #	5-Date Shift Code
6-Production QC data review. (List # of different production runs for which data provided, quantity of charges made, and time span over which production runs were made; ex. 4 production runs, totaling 2000 charges, from 01/99 through 05/00).				
7-Describe how charges verified to be same as those selected by witness? (Either charge selection done at same time as QC shots and in sight all time since selected, or seal / marking must match description in Charge Selection Loading Section.)				
8-QC set-up same as listed for production shots? (Y / N) Document#: _____ Revision: _____		9-# of shots made (6 minimum)	10-Comparison of witnessed results to production data (Ex. 10% higher, within 5%, etc.)	
11-Miscellaneous comments on QC shots				

Witness Information

12-Name	13-Company	14-Signature
15-Name	16-Company	17-Signature

Original sent to API by witness
Copy retained by witness and testing company



GENERAL INFORMATION

1-Testing Company	2-Perforating System Description (Include gun and charge name)	3-Test Location (City, State, Country)
-------------------	--	--

OTHER WITNESS TASKS

5. Target Pouring – Optional activity to witness, API RP 19B, Section 1.2

1-Date	2-Target Diameter	3-Casing Diameter	4-Casing Wall
5-Casing (Verify that the casing used in the construction of the target meets the reported grade and weight)			
6-# of Concrete Trucks	7-Slurry information verified for each truck (Y / N) (Specifications listed in Mandatory Gun Firing / Data Collection Section)		8-Slurry sample taken from middle of target? (Y / N)
9-Miscellaneous comments on Target Pouring			

Witness Information

10-Name	11-Company	12-Signature
---------	------------	--------------

6. Briquette Preparation – Optional activity to witness, API RP 19B, Section 1.2

1-Specimens prepared per RP19B? (Y / N) (Each compartment filled half full, then puddled 25 times each with a glass or non-corroding metal rod ¼ in. in diameter, then filled completely, then puddled 25 times, then excess slurry struck even with top of mold)	2-# of Specimens Prepared (Minimum required is six)
3-Miscellaneous comments on Briquette Preparation	

Witness Information

4-Name	5-Company	6-Signature
--------	-----------	-------------

7. Briquette Testing – Optional activity to witness, API RP 19B, Section 1.2

1-Description of testing machine (Include Make and Model #)	2-Calibration on machine current? (Y / N) (Required every two years)
3-Approximate time to crush specimens (Maximum load should be reached between 20 and 80sec. The rate of loading shall be 16,000, ±1600 lbf (4000 ±400 psi) per minute)	
4-# of Specimens tested	5-Description of crushed specimens (Ex: Pyramid shaped, sheared at 45 deg angle, etc.)
6-Crush Test Results? (List all individual specimen results)	
7-Miscellaneous comments on Briquette Testing	

Witness Information

8-Name	9-Company	10-Signature
--------	-----------	--------------

8. Gun Firing / Data Collection – Optional activity to witness, API RP 19B, Section 1.9.3

1-Burr Height Measurements (Describe how verified; ex. 100% of measurements witnessed, or specific individual shots checked against datasheet)
2-Miscellaneous comments on Gun Firing / Data Collection

Witness Information

3-Name	4-Company	5-Signature
--------	-----------	-------------



API Witness Report – Perforator System Registration

GENERAL INFORMATION

1-Testing Company	2-Perforating System Description (Include gun and charge name)	3-Test Location (City, State, Country)
-------------------	--	--

9. RE-CERTIFICATION - QC SHOTS – Mandatory activity to witness API RP 19B, Section 1.11

1-Date	2-Location (If different from test location)	3-Charge Description	4-Charge Part #	5-Date Shift Code
6-Re-Certified Design Name(s) as it appears on the API Web Site. (List all the applicable system names below).				
7- Quantity of Charges Available for Selection Process. (Minimum required of 300, as defined per API RP 19B, Section 1.4; less than 12 months old).				
8-Describe how charges verified to be same as those selected by witness? (Either charge selection done at same time as QC shots and in sight all time since selected, or seal / marking must match description in Charge Selection Loading Section.)				
9- Test configuration. (QC test shall be conducted as defined in the original QC specification)				
10- QC Shot targets (Verify the quality of QC shot targets against the original QC specification)				
11-QC set-up same as listed for production shots? (Y / N)	12-# of shots made (a minimum of 6 valid test shots shall be made)	13-Comparison of witnessed results to the original specification data (must meet or exceed the original QC specification, 90% or higher.) (Y / N)		
Document#:	Revision:			
14-Miscellaneous comments on QC shots				

Witness Information

15-Name	16-Company	17-Signature
18-Name	19-Company	20-Signature

Use this page and copies of this page to document additional comments, concerns and / or remarks.

Original sent to API by witness
Copy retained by witness and testing company

