Date of Issue: April 2015

Affected Publication: API Standard 675, *Positive Displacement Pumps—Controlled Volume for Petroleum, Chemical, and Gas Industry Services*, Third Edition, November 2012

ERRATA 2

(incorporates changes from Errata dated June 2014)

Page 1, **Section 1, Scope***, replace the* NOTE *to read:*

NOTE See API 674 for positive displacement reciprocating pumps and API 676 for positive displacement rotary pumps.

Page 1, **Section 1, Scope***, add the following* NOTE *to the end of the section:*

NOTE A bullet (•) at the beginning of a paragraph indicates that either a decision is required or further information is to be provided by the purchaser. This information should be indicated on the data sheets (see Appendix A); otherwise, it should be stated in the quotation request or in the order.

*Page 64***, F.1.5, Inlet Pressure versus Liquid Vapor Pressure**, *replace the equation as follows:*

$$P_{min} > 1.1 \cdot P_v \qquad \text{(F.4)}$$

where

P_v is the highest liquid vapor pressure or the gas dissolution pressure, expressed in kilopascals (pounds force per in^2).

Multiple pages. Insert a bullet (•) that indicates information or a decision is required from the purchaser before each paragraph indicated below.

6.1.1	6.14.6.4	8.2.3.3
6.1.4	6.14.6.5	8.2.3.4
6.1.5	6.15.3	8.2.4.2
6.1.8	7.2.2.1	8.3.1.2
6.1.13	7.2.2.2	8.3.4.2
6.1.21	7.2.2.3	8.3.4.2.1
6.3.1	7.3.1	8.3.4.2.2
6.4.1	7.3.2	8.3.5.1
6.5.3	7.3.7	8.3.5.2
6.14.2.4	7.3.12	8.3.7
6.14.2.8	7.3.13	8.3.7.1
6.14.2.11	7.3.16	8.3.7.2
6.14.2.12	7.3.18	8.3.7.3
6.14.2.20	7.3.19	8.3.7.4
6.14.3.6	7.4.2.1	8.3.8
6.14.5.1	7.8.1	8.4.1
6.14.5.4	8.1.2	8.4.8
6.14.5.4 d)	8.1.5	
6.14.6.1	8.1.8	